

GDLM-A-0020-WTA-16



Key Features:

High Reliability
 Compactable size
 Auto Power Control
 Low Power Consumption
 Wide Operating Temperature

Applications:


Beam Splitting
 Line Laser Levels
 Surveying Equipment
 Laser Alignment & Pointing

Model Number		GDLM-A-0020-WTA-16			
Optical Parameters		Specs			Conditions
		Min	Typ	Max	
Wavelength		531nm	532nm	533nm	
Output Power		18mW	20mW	22mW	At 25 °C
Power Stability	2hours @ Constant Temp	-	-	+/-10%	APC
	Over Operating Temp Range	15mW	-	25mW	
Operating Temperature (Case)		10~+40 °C	0~+45 °C	-	APC
Residual IR		-	-	1%	
Beam Diameter		-	5mm	-	At 10m
Beam Divergence		-	0.5mrad	-	Full angle
Roundness		70%	80%	100%	
Warm Up Time		-	1s	-	0~45 °C
Electrical Parameters					
LD Working Current		-	420mA ^①	700mA	0~45 °C
LD Working Voltage		1.6V	1.9V	2.2V	
Monitor Current		50uA	-	300uA	
GDL Power Consumption		-	0.80W ^②	1.54W	0~45 °C
Mechanical Parameters					
Laser Head Dimensions	Length	-	-	30mm	
	Diameter	11.85mm	11.9mm	11.95mm	
Beam Alignment Tolerance	Position(Δr)	-	0.3mm	0.5mm	
	Angle	-	7mrad	17.5mrad	
Reliability					
Storage Temperature		-	-20 to +60 °C	-	
Shock		-	1000g, 1ms, 6 shocks	-	3 axes, 2 shocks/axis
Vibration		-	20~2000Hz, 0.02g ² /Hz	-	3 axes, 1hr/axis
Expected Lifetime (MTTF)		5000hrs	-	-	Room temperature

Note: ^①20mW at 25 °C

^②20mW at 25 °C

Typical Output Performance



Dimensions and Pin Configuration (Unit: mm)

